

## SPECTRA Keypads LCD



### K32LCD+ Wired LCD Keypad

#### ► Features

- Controls and displays up to 32 zones in 2 partitions
- 8 one-touch action buttons
- 3 keypad-activated panic alarms
- 32-character, blue LCD with programmable labels
- Menu-driven programming for easy system setup (installer and end-user)
- StayD™ status LED
- Independently-set chime zones
- Separate Arm, Sleep, Stay, and Off LEDs per partition
- Adjustable key backlight, contrast and scroll speed
- Multilingual display
- In-field firmware upgradeable via 307USB

#### ► Specifications

Input Voltage	12 to 14 Vdc
Current Consumption	Typical: 43mA Maximum: 86mA
Keypad Zone Input	1
Connections	4-wire expansion bus
Operating Temperature	-10 to 55 °C (14 to 131 °F)
Dimensions	12.6 x 15 x 2.7 cm (5 x 5.9 x 1.1 in.)



### K35 Wired Fixed LCD Keypad

#### ► Features

- Controls and displays the status of 32 zones in 2 partitions
- 8 one-touch action buttons
- 3 keypad-activated panic alarms
- Fixed message display that guides you in the operation of the system
- StayD™ status icon
- Displays Arm, Sleep, Stay and Disarmed status for each partition
- Displays troubles, bypassed zones and alarm memory
- Adjustable backlight
- Independently set chime zones
- Available in multiple languages
- In-field firmware upgradeable via 307USB

#### ► Specifications

Input Voltage	12 to 14 Vdc
Current Consumption	Typical: 38mA Maximum: 103mA
Keypad Zone Input	1
Connections	4-wire expansion bus
Operating Temperature	0 to 50 °C (32 to 122 °F)
Dimensions	12.3 x 14.4 x 3.2 cm (4.9 x 5.7 x 1.3 in.)