

SPECTRA Keypads LCD



K37 Wireless Fixed LCD Keypad

► Features

- Controls and displays the status of 32 zones in 2 partitions
- 8 one-touch action buttons
- 3 keypad-activated panic alarms
- Fixed message display that guides you in the operation of the system
- StayD™ status icon
- Displays Arm, Sleep, Stay and Disarmed status for each partition
- Displays troubles, bypassed zones and alarm memory
- Goes into Standby Mode after 20 seconds to save battery life, but remains synchronized with the panel to automatically re-activate upon an entry delay or alarm
- Adjustable backlight
- Independently set chime zones
- Can be used with external 6VDC power adapter as an alternative power source (PA6 not included)
- Available in multiple languages
- In-field firmware upgradeable via 307USB

► Specifications

Input Voltage	Primary Power: 6 Vdc (300 mA) Backup Power: 2 x AA batteries
RF Frequency	433 or 868 MHz
Battery Life	Up to 1 year
Wireless Range	40m (130 ft) typical in residential environment
Operating Temperature	0 to 50 °C (32 to 122 °F)
Dimensions	12.3 x 14.4 x 3.2 cm (4.9 x 5.7 x 1.3 in.)

SPECTRA Keypads LED



K32RF Wireless LED Keypad Module

► Features

- Controls and displays up to 32 zones and 2 partitions
- 8 one-touch action buttons
- 3 keypad-activated panic alarms
- StayD™ Status LED
- Separate Arm, Sleep, Stay, and Off LEDs per partition
- Adjustable key backlight
- Available in multiple languages
- In-field firmware upgradeable via 307USB

► Specifications

Input Voltage	Primary Power: 6 Vdc (300 mA) Backup Power: 3.7 Vdc Li-ion rechargeable
RF Frequency	433 or 868 MHz
Battery Life	Up to 48 hours
Wireless Range	40m (130 ft) typical in residential environment
Connections	4-wire expansion bus
Operating Temperature	0 to 50 °C (32 to 122 °F)
Dimensions	12.2 x 14.7 x 3.4 cm (4.8 x 5.8 x 1.3 in.)