

16/32CH2U16PoE Network Video Recorder



Features

- > Up to 16/32 channel IP camera input
- > H.264/MJPEG dual codec decoding
- > Max 200Mbps incoming bandwidth
- > Up to 5Mp resolution preview&playback
- > HDMI/VGA/TV simultaneous video output
- > 16 channel synchronous realtime playback, GRID interface
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.
- > ONVIF Version 2.3 conformance
- > 3D intelligent positioning with PTZ camera
- > Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 3 USB(1 USB3.0)
- > Support IPC UPnP, 16PoE ports
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

Technical Specifications


Model	NVR4816-16P	NVR4832-16P
System		
Main Processor	Dual-core embedded processor	
Operating System	Embedded LINUX	
Video& Audio		
IP Camera Input	16 channel	32 channel
Two-way Talk	1channel Input, 1channel Output,RCA	
Display		
Interface	1 HDMI,1 VGA,1 TV	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	
Display Split	1/4/8/9/16	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Recording		
Compression	H.264/MJPEG	
Resolution	5Mp (2560×1920) /3Mp (2048×1536) /1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)&etc.	
Record Rate	200Mbps	
Bit Rate	48~ 8192kbps	
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop	
RecordInterval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection & Alarm		
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email,FTP, Snapshot, Buzzer & Screen tips	
Video Detection	Motion Detection,MDZones: 396(22×18), Video Loss & Camera Blank	
Alarm Input	16channel	
Relay Output	4channel	
Playback & Backup		
Sync Playback	1/4/9/16	
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search	
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom	
Backup Mode	USB Device/Network/Internal SATA burner/eSATADevice	
Network		
Ethernet	1 RJ-45 port (10/100/1000Mbps)	
PoE	16 ports (IEEE802.3at/af)	
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support IP camera, DVR, NVS and etc.)	
Max. UserAccess	128users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
Storage		
Internal HDD	8 SATA ports, up to 32TB	

NVR4816/4832-16P



External HDD	1 eSATA port
Auxiliary Interface	
USB	3 ports (1 Rear USB3.0, 2 Front USB2.0)
RS232	1 port, For PC communication& Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	AC 100V~240V,50/60HZ
Power Consumption	40W(without HDD)
Working Environment	-10°C ~ +55°C / 10%~90%RH / 86~106kpa
Dimension (W×D×H)	2U, 440mm×460mm×89mm
Weight	6.5KG(without HDD)

System Connection



Belco Security Sdn Bhd

No.14 Jalan Intan 1,
Taman Puchong Intan,
47150 Puchong, Selangor, Malaysia.

Email: sales@belco.com.my

www.belco.com.my

*Design and specifications are subject to change without notice.

© 2015 Belco Security Sdn Bhd