

Wireless Sirens



SR130

Wireless Outdoor Siren with Built-in Strobe Light

► Features

- Built-in transceiver
- Wireless siren (100 dBA) with integrated strobe light
- Fast alarm response time (within 4 seconds)
- 2.5 hour alarm display (strobe flashes every 4 seconds after bell cutoff)
- Siren presence supervised by control panel
- Dual tamper mechanism (wall / cover)
- Siren test mode
- Signal strength / RF transmission and status LEDs
- Strobe lens available in 3 colors (red, blue and amber)
- In-field firmware upgradeable via 307USB

► Specifications

Power Supply	3 x C alkaline batteries (4.5 Vdc)
RF Frequency	Built-in transceiver 433 or 868 MHZ
Battery Life	3 years (typical use)
Wireless Range	Typical residential environment 35m (115 ft) with all-in-one consoles 70m (230 ft) with MG5000, MG5050 and RTX3
Siren	100 dBA
Humidity	5 to 95%
IP Rating	IPX4
Operating Temperature	-25° to 55° C (-13° to 131° F)
Dimensions	13.4 x 21.17 x 5.1 cm (5.29 x 8.34 x 2.01 in.)



SR150

Wireless Outdoor Siren with Built-in Strobe Light

► Features

- Built-in transceiver
- Wireless siren (100 dBA) with integrated strobe light
- Weather-resistant design using a PC / ABS enclosure with UV protection and a silicone coated PCB (-20 to 50 °C / -4 to 122 °F)
- Battery powered with optional external AC / DC power
- Fast alarm response time (4 seconds)
- 2.5 hour alarm display (strobe flashes every 4 seconds after bell cut-off)
- Siren presence supervised by control panel
- Dual tamper protection (cover removal, and removal from wall)
- Siren test mode
- 4-LED signal strength and status display
- Strobe lens available in 4 colors (red, blue, amber, and clear)
- In-field firmware upgradeable via 307USB

► Specifications

Power	3 x D alkaline batteries (4.5 Vdc) - Optional 8 to 16 Vac / 9 to 20 Vdc external power
Battery Life	Up to 3 years (typical use)
Current Consumption	Sleep: 22 uA Standby: 130 uA Alarm: 550 mA
Wireless Range	Typical residential environment 35m (115 ft) with all-in-one consoles 70m (230 ft) with MG5000, MG5050, RTX3 and K32LX
Siren	100 dBA (1 meter)
Humidity	93%
IP Rating	IPX4
Operating Temperature	-30 to 50 °C (-22 to 122 °F)
Dimensions / Weight	24 x 6 x 18 cm (9.5 x 2.3 x 7 in.) / 1.08 kg (2.4 lb) without batteries