

Product model		UT-600X series
Number of serial port		4
Processor		32bit 150MHz
Internal storage		32M bytes
Serial port	Baud rate	300-921600bps
	Check bits	None, Odd, Even, Mark, Space
	Data bits	5, 6, 7, 8
	Stop bits	1, 1.5, 2
	Flow control	RTS/CTS, XON/XOFF
	Serial port form	RJ45/ wiring terminal
	Serial port protection	(Contact ±6KV, air ±8KV) antistatic protection, surge 10/700us common mode/difference mode 0.5KV
	Signal	RS232: RXD/TXD/DTR/GND/DSR/RTS/CTS, RS422: TXD+/RXD+/TXD-/RXD-/GND, RS485: Data+/Data-
Internet access	Rate	10/100M self-adaption
	Internet access form	RJ45
	Internet access protection	Embedded 2KV electromagnetic isolation, surge 10/700us common mode: 2000V/difference mode 1000V
Software	Protocol	ARP, IP, ICMP, UDP, TCP, HTTP, TELNET, DNS, DHCP
	COM Virtual COM	Windows 2000/XP/7/8/10 32/64bit
Environment	Operating temperature	-40℃——85℃
	Operating humidity	5%——95%
	Storage temperature	-40℃——85℃
	Storage humidity	5%——95%
Authentication		FCC, CE
Power supply		DC12~60V, 350mA @12Vmax (customizable 5V)
		Surge 1.2/50us Common mode: 2000V/difference mode 1000V
Appearance	Material	Metal shell
	Dimension	160 mm×90 mm×30 mm